

ZEBRA

SUGGESTED

APPLICATIONS

Shelf labeling

Work in process

Z-Xtreme 2000T Removable


FEATURES

- · Thermal transfer, matte polyester label with a removable acrylic adhesive
- Some smear/scratch resistance
- Good durability and chemical resistance
- Topcoating is suitable for fanfolding
- Available in white (66760RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper	
Facestock	White or silver matte coated polyester	2.3 mil	
Adhesive	Removable, acrylic- based	1.0 mil	
Liner	50 lb. semi-bleached, kraft stock	3.2 mil	
	TOTAL ± 10%	6.5 mil	

ADHESIVE STRENGTH



TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
50° F (10° C)	-40° F to 302° F -40° C to 150° C	72° F (22° C) at 50% RH

Expected Exterior Life 3 years

CHEMICAL RESISTANCE

		Suggested Ribbon			
	Chemical	6100	3200	6200	5095
	Blood	•	•	•	•
	Body Fluid	•	•	•	•
Weak	Salt Water	•	•	•	•
>	Water	•	•	•	•
	Window Cleaner	•	•	•	•
a)	Alcohol	•			
Moderate	Ammonia	•	•	•	•
Nod	Bleach	•	•	•	•
	IPA	•	•	•	•
_	Gasoline	NR	NR	NR	NR
Harsh	Grease	NR	NR	NR	NR
_	Oil	NR	NR	NR	NR
	Acetone	NR	NR	NR	NR
Je	IR Reflow	NR	NR	NR	NR
Extreme	MEK	NR	NR	NR	NR
ш	TCE	NR	NR	NR	NR
	Xylene	NR	NR	NR	NR

Recommended
Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com