



ZEBRA

8000T Nylon 5.7mil Tag

FEATURES

- Thermal transfer, woven nylon 5.7 mil tag
- Excellent cross- and machine-directional tear strength
- Soft fabric may be preferable in applications in contact with human skin
- Available in white (65997RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White woven nylon	5.7 mil
TOTAL ± 10%		5.7 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
N/A	-40° F to 302° F (-40° C to 150° C)	72° F (22° C) at 50% RH

Expected Exterior Life
2 years

CHEMICAL RESISTANCE

		Suggested Ribbon
Chemical		Nylon Ribbon
Weak	Blood	●
	Body Fluid	●
	Salt Water	●
	Water	●
	Window Cleaner	●
Moderate	Alcohol	●
	Ammonia	●
	Bleach	●
	IPA	●
Harsh	Gasoline	●
	Grease	●
	Oil	●
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Sew-in garment labeling



- Seat belt labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.