



ZEBRA

PolyPro 3000T Gloss Removable

FEATURES

- Thermal transfer, polypropylene label
- Recommended for labeling applications requiring clean removability
- Available in white (10030763RM)
- May be used in desktop printers
- For best performance use 5095 ribbon

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White topcoated polypropylene film	3.6 mil
Liner	50 lb. kraft stock	3.2 mil
Adhesive	Removable acrylic	.6 mil
TOTAL ± 10%		8.5 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
32° F (0° C)	-40° F to 180° F (-40° C to 82° C)	72° F (22° C) at 50% RH

Expected Exterior Life

Up to 1 year

CHEMICAL RESISTANCE

		Suggested Ribbon	
		Chemical	5095
Weak	Blood	●	●
	Body Fluid	●	●
	Salt Water	●	●
	Water	●	●
	Window Cleaner	●	●
Moderate	Alcohol	●	●
	Ammonia	●	●
	Bleach	●	●
	IPA	●	●
Harsh	Gasoline	●	●
	Grease	●	●
	Oil	●	●
Extreme	Acetone	●	●
	IR Reflow	●	●
	MEK	●	●
	TCE	●	●
	Xylene	●	●

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Temporary parking identification



- Window labeling



- Work in process labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

© 2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.