

Z-Select 2000D Label

Direct thermal label with a permanent rubber adhesive

Whether you are printing shipping, picking and receiving labels in a warehouse, or product or pricing labels, you need reliable, high-quality printing. Zebra's direct thermal Z-Select 2000D label provides just that. Designed with reliability and print quality in mind, the Z-Select 2000D features a protective topcoat, offering improved printhead life and resistance to moisture, oils and other environmental factors. Featuring a permanent, low temperature adhesive, Z-Select 2000D provides consistent quality so you can count on optimized performance – with each and every label. Z-Select 2000D labels are recommended for a wide variety of labelling applications and surfaces.



Specially coated for trouble-free printing

Z-Select 2000D labels feature a protective topcoat for ultra-smooth printing that preserves the printhead of your printer. You also get excellent print quality and sharp definition. And the coating offers enhanced resistance to moisture, oils and other environmental factors to increase the durability of your labels.

Direct Thermal Material

Z-Select 2000D is a direct thermal material, meaning no ribbon is required for printing and so only one stock item is required.

Optimized for use with food products and in cold environments

With its all-temperature permanent rubber adhesive, these labels can be securely applied in temperatures as low as 0° C and will remain adhered in temperatures up from -40°C up to 50°C, making them perfect for use on assets in cold environments. The adhesive complies with European food regulation EC 1935/20004, EU 10/2011 and BfR Recommendation XXI for direct contact with dry and moist non-fatty foodstuffs. It also meets FDA 175.105 for direct contact with dry foodstuffs.

Zebra ZipShip – on the shelf and ready to ship

Need your label in a hurry? Z-Select 2000D labels are part of our Zebra ZipShip program— on the shelf and ready for immediate dispatch. You get fast shipment - and the minimum order is just one box.

Print Confident. Print Quality. Print Zebra.

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pre-test our own line of thermal printing supplies to ensure consistent, optimized performance. We utilize an ISO 9001 certified, 23-point inspection process and consistent materials to ensure reliable performance from order-to-order. No matter when you order your labels, you can count on the same consistent performance.

Z-Select 2000D Label – delivers high-quality print, with an all-temp permanent adhesive for labeling in cold environments.
For more information, please visit www.zebra.com/barcodesupplies

Specifications

| Material Construction | |
|--|--|
| Raw Material Number | 05311RM |
| Facestock | Matte white topcated thermal imaging paper 81 microns |
| Adhesive | Permanent rubber adhesive 13 microns |
| Liner | 62gsm glassine liner 51 microns |
| Total Thickness (+/-10%) | 145 microns ± 10% |
| Environment | Indoor |
| Temperature Performance | |
| Minimum Application Temperature ¹ | 0°C |
| Service Temperature Range ² | -40°C to 50°C |
| Recommended Printers and Ribbons | |
| Printers | Mobile, desktop, mid-range and high-performance thermal printers |
| Ribbons | N/A |
| Adhesive Strength | |
| Corrugate | No Data available |
| Steel | No Data available |
| Polycarbonate | No Data available |
| Polyethylene | No Data available |
| Chemical Resistance | |
| Weak Chemicals | |
| Blood | Test in your application |
| Body Fluid | Test in your application |
| Salt Water | Test in your application |
| Water | Test in your application |
| Window Cleaner | Test in your application |
| Moderate Chemicals | |
| Alcohol | Not recommended |
| Ammonia | Not recommended |
| Bleach | Not recommended |
| IPA | Not recommended |
| Harsh Chemicals | |
| Gasoline | Not recommended |
| Grease | Not recommended |
| Oil | Not recommended |
| Extreme Chemicals | |
| Acetone | Not recommended |
| IR Reflow | Not recommended |
| MEK | Not recommended |
| TCE | Not recommended |
| Xylene | Not recommended |

| UL/cUL Certified Materials with this Ribbon | |
|---|---|
| N/A - No ribbon needed | |
| Regulatory and Compliance | |
| EC 1935/2004, EU 10/2011 and BfR Recommendation XIV for direct contact with dry and moist, non-fatty foodstuffs; FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier; BPA and latex free | |
| Product Performance and Suitability | |
| Recommended storage conditions | 6 month duration when stored at 20°C to 25°C at 40% to 50% RH |
| Expected life span in application ³ | Indoor use for up to 1 year |
| Sample Part Number | SAMPLE5311/SAMPLE5311-D |

Material Testing in End Application

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

Warranty

Supplies are warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For the complete warranty statement, please visit www.zebra.com/warranty.

- Footnotes**
1. When the label is applied, the environment and surface should be above this temperature.
 2. Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range.
 3. Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated.

Markets and Applications

- Logistics**
- Labeling of packaging materials, e.g. boxes and pallets
- Warehousing**
- Shipping labels
 - Picking labels
 - Receiving labels
- Retail**
- Shelf edge labels
 - Product labels
 - Price labels
- Healthcare**
- Sterile services labels
- Manufacturing**
- Work-in-progress labels
- Other**
- Product identification labels



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
zebra.com/locations
la.contactme@zebra.com