

## Xi4 Printer

Specifications are provided for reference and are based on testing the Xi4™ printer using genuine Zebra® supplies. Results may vary in actual application settings or when using other-than-recommended Zebra supplies. Zebra recommends always qualifying any application with thorough testing.

### STANDARD FEATURES

#### Printer Options

- Full-function front panel and large multilingual back-lit LCD display with user-programmable password protection
- Clear media side door allows easy monitoring of supplies usage without opening the printer
- Thin film printhead with E3™ Element Energy™ Equalizer
- 64 MB on-board linear Flash memory
- Serial RS-232 and bi-directional Parallel ports with auto detect
- USB 2.0 port
- Dual media sensors — transmissive and reflective selectable through software or front panel
- Internal ZebraNet™ 10/100 Print Server supports 10Base-T, 100Base-TX, and fast Ethernet 10/100 auto-switching networks

#### Firmware

- ZPL® or ZPL II® programming language — selectable through software or front panel
- XML-Enabled Printing — direct connect integration for barcode label printing; eliminates license fees and print server hardware and lowers customization and programming costs

### OPTIONAL FEATURES

#### Printer Options

- Clear media side bi-fold door allows shorter media door opening radius
- Full-width rotary knife cutter and catch tray operates under software control cutting labels individually or in strips



- Media rewind spindle rewinds finished roll internally onto 3" (76 mm) core or enables label peel and liner rewind
- Applicator interface — provides status and control signals for applicators and remote control devices
- Media supply spindle for 3" (76 mm) core or 40 mm core
- Additional fonts

#### ZebraNet Print Server Options

- Features provided by ZebraNet Print Servers include:
  - **Web View** web pages connect and control Zebra barcode printers via the printer's web interface using common Internet browsers
  - **Alerts** provides alerts via any e-mail-enabled, wired, or wireless device to minimize downtime
- ZebraNet b/g Print Server
- ZebraNet Wireless Plus Print Server
- SEH PS102-Z Internal IPV6 Print Server

## OPTIONAL FEATURES (continued)

### Printer Operation

- 32 bit 133 MHz RISC processor
- 16 MB SDRAM memory
- Internal real-time clock
- Advanced label / media counters
- Thermal transfer and direct thermal printing of barcodes, text and graphics
- Auto calibration when printer is turned on or when printhead is closed using approximately two labels
- Early Warning Systems provide low label, low ribbon, and clean printhead alerts via the front panel and ZebraLink™ Alerts
- Zebra Universal Printer Driver for Microsoft® Windows® 2000 / XP / Vista® operating systems

### Firmware Options

Zebra's Alternative Programming Language (APL) allows integration into mixed printer environments without re-programming formats. Available through Development Services.

## ZEBRALINK SOLUTIONS

**ZebraDesigner™ Pro** — An intuitive, easy-to-use software program for creating complex label designs (option)

**ZebraDesigner** — Offers basic features for simple label design

**ZebraDesigner for myXML** — Easy-to-use label design software that enables printing on XML enabled printers

**ZebraNet Bridge Enterprise** — Centrally manage Zebra printers from a computer anywhere on your network

**ZebraNet Utilities v 7.0** — Provides enhanced printing, conversion, and administration capabilities; message management; and more

## MEDIA SPECIFICATIONS

- Media type: Continuous, die-cut, or black mark, notch.
- Minimum label length\*:
  - Rewind mode: 0.25" (6 mm)
  - Peel mode: 0.5" (13 mm)
  - Tear-off mode: 0.7" (18 mm)
  - Cutter mode: 1.5" (38 mm)
- Media thickness (label and liner): 0.003" (0.076 mm) to 0.012" (0.305 mm)
- Maximum media roll size: 8.0" (203 mm) outside diameter on a 3" (76 mm) inside diameter core
- Transmissive (gap) sensing standards:
  - Inter-label gap: 2 mm – 4 mm, preferably 3 mm
  - Sensing notch: 0.25" W (6 mm) x 0.12" L (3 mm)
  - Sensing hole: 0.125" (3 mm) diameter
- Reflective (black mark) sensing standards:
  - Black mark length (parallel to inside media edge): 0.12" to 0.43" (3 mm to 11 mm)
  - Black mark width (perpendicular to inside media edge): 0.43" (>11 mm)
  - Black mark location: within 0.040" (1 mm) of inside media edge
  - Black mark density: >1.0 Optical Density Units (ODU)
  - Maximum media density: 0.5 ODU

## RIBBON SPECIFICATIONS

- Standard lengths: 1476' (450 m) or 984' (300 m) provides 2:1 and 3:1 media roll to ribbon ratios
- Maximum ribbon roll size: 3.2" (81.3 mm) outside diameter on a 1.0" (25.4 mm) inside diameter core
- Ribbon wound coated-side out

\*Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.

## FONT SPECIFICATIONS

- Bitmap fonts A through H and GS symbols are expandable up to 10 times, height and width independent
- Smooth scalable font Ø (CG Triumvirate™ Bold Condensed\*) is expandable dot-by-dot, height and width independent
- IBM Code Page 850 International Characters
- 61 MB user available non-volatile memory storage for downloadable objects
- 12 MB user-available SDRAM

\*Contains UFST® from Agfa Monotype Corporation

## COMMUNICATIONS SPECIFICATIONS

- ZebraNet Internal Wireless Plus Print Server supports advanced wireless securities through an integrated, internal, theft-resistant radio card
- ZebraNet Wireless Plus Print Server supports advanced wireless securities through an external radio card
- ZebraNet 10/100 Print Server supports 10Base-T, 100Base-TX, and fast Ethernet 10/100 auto-switching networks
- Support for ZebraNet PrintServer II 10Base-T Ethernet network
- USB 2.0 — 12 Mbits / second
- High-speed bi-directional Parallel interface — IEEE 1284-1994 compatibility, ECP, nibble mode
- High-speed serial interfaces:
  - RS-232C with DB9F connector, optional converter for DB25F available
  - Optional RS-422/485 with multidrop capability to network multiple printers from a single host with external adapter
  - Software (XON/XOFF) or hardware (DTR/DSR) communication handshake protocols
- IBM Twinax interface emulates IBM System 3x and IBM AS/400® printers
- IBM Coax interface emulates IBM System 3270 printers
- Applicator interface with DB15F connector

## ZEBRA PROGRAMMING LANGUAGE (ZPL AND ZPL II)

- Communicates in printable ASCII characters
- Unicode™-Compliant (Version V53.17 and higher)
- Compatible with mainframe, mini, and PC hosts
- Downloadable objects include graphics, scalable and bitmap fonts, label templates, and formats
- Object copying between memory areas (RAM, Onboard Flash memory locations)
- Adjustable print cache
- Data compression
- Automatic memory allocation for format while printing
- Automatic serialization of fields
- Format inversion (white on black)
- Mirror-image printing
- Four position field rotation (0°, 90°, 180°, 270°)
- Slew command
- Programmable label quantities with print, pause, cut control
- User-programmable password
- Status messages to host on request

## BARCODE SYMBOLOGIES AND SPECIFICATIONS

- Barcode Ratios: 2:1, 7:3, 5:2, and 3:1
- Linear Barcodes: Code 11, Code 39, Code 93, Code 128 with subsets A / B / C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-digit or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
- 2D Barcodes: Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, TLC 39, MicroPDF, RSS-14 (and composite), Aztec

## 110XI4™ 203 DPI

### Printing Specifications

- 203 dpi resolution (8 dots / mm)
- Dot size (W × L): 0.0049" × 0.0049" (0.125 mm × 0.125 mm)
- First dot location measured from inside media edge: 0.14" ±0.05" (3.5 mm ±1.25 mm)
- Maximum print width: 832 dots 4.09" (104 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 150" (3810 mm)
- Media registration tolerance\*:
  - Vertical:
    - ±0.030" (±0.75 mm) at print speeds at or below 4 ips on non-continuous media
    - ±0.060" (±1.5 mm) at print speeds higher than 4 ips
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 2.4, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 4.9 mil to 49 mil
  - Ladder (rotated) orientation: 4.9 mil to 49 mil

### Media and Ribbon Specifications

- Media width (label and liner): 0.79" (20 mm) to 4.5" (114 mm)
- Minimum label length: see media specifications on page 2
- Maximum full-width media thickness for cutter: 0.009" (0.23 mm)
- Ribbon width: 0.79" (20 mm) to 4.33" (110 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 121 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 10.31" (261.9 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 50 lbs. (22.7 kg)
- RFID ready is standard (UHF EPC Gen 2, Class 1 compliant)

## STANDARD PRINTER FONTS

Fonts A through V are Expandable up to 10 times, height and width independently. Fonts E and H, however are not considered "in-spec" (OCR-A and OCR-B) when expanded.

The scalable smooth font Ø is expandable on a dot-by-dot basis, height and width independent, while maintaining smooth edges. Maximum character size depends on available memory. IBM Code Page 850 international character sets are available in fonts A through G, and O through software control.

## FONT MATRICES: 203 DPI (8 DOTS / MM) PRINTHEADS

Font	Matrix (in dots) (H × W)	Type†	Minimum Character Size (H × W) in inches (mm)	Max CPI
<b>A</b>	9 × 5	U-L-D	0.044 × 0.029 (1.1 × 0.74)	33.9
<b>B</b>	11 × 7	U	0.054 × 0.044 (1.37 × 1.1)	22.6
<b>C, D</b>	18 × 10	U-L-D	0.088 × 0.059 (2.2 × 1.5)	16.9
<b>E</b>	28 × 15	OCR-B	0.138 × 0.098 (3.5 × 2.5)	10.1
<b>F</b>	26 × 13	U-L-D	0.128 × 0.079 (3.3 × 2.0)	12.7
<b>G</b>	60 × 40	U-L-D	0.295 × 0.236 (7.5 × 6.0)	4.2
<b>H</b>	21 × 13	OCR-A	0.103 × 0.093 (2.6 × 2.4)	10.7
<b>GS</b>	24 × 24	SYMBOL	0.118 × 0.118 (3.0 × 3.0)	8.4
<b>P</b>	20 × 18	U-L-D	0.098 × 0.089 (2.50 × 2.25)	N / A
<b>Q</b>	28 × 24	U-L-D	0.138 × 0.113 (3.50 × 3.00)	N / A
<b>R</b>	35 × 31	U-L-D	0.172 × 0.153 (4.38 × 3.88)	N / A
<b>S</b>	40 × 35	U-L-D	0.197 × 0.172 (5.00 × 4.38)	N / A
<b>T</b>	48 × 42	U-L-D	0.236 × 0.207 (6.00 × 5.25)	N / A
<b>U</b>	59 × 53	U-L-D	0.290 × 0.261 (7.38 × 6.63)	N / A
<b>V</b>	80 × 71	U-L-D	0.394 × 0.349 (10.0 × 8.88)	N / A
<b>Ø</b>	variable	U-L-D	variable	N / A

† U = Uppercase L = Lowercase D = Descenders

\*Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.

## 110XI4 300 DPI

### Printing Specifications

- 300 dpi resolution (11.8 dots / mm)
- Dot size (W × L): 0.0033" × 0.0039" (0.084 mm × 0.01 mm)
- First dot location measured from inside media edge: 0.08" ±0.05" (2.1 mm ±1.25 mm)
- Maximum print width: 1248 dots 4.16" (105.7 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 100" (2540 mm)
- Media registration tolerance\*:
  - Vertical:
    - ±0.030" (±0.75 mm) at print speeds at or below 4 ips on non-continuous media
    - ±0.060" (±1.5 mm) at print speeds higher than 4 ips
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 2.4, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 3.3 mil to 49 mil
  - Ladder (rotated) orientation: 3.9 mil to 39 mil

### Media and Ribbon Specifications

- Media width (label and liner): 0.79" (20 mm) to 4.5" (114 mm)
- Minimum label length: see media specifications on page 2
- Maximum full-width media thickness for cutter: 0.009" (0.23 mm)
- Ribbon width: 0.79" (20 mm) to 4.33" (110 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 121 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 10.31" (261.9 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 50 lbs. (22.7 kg)
- RFID ready is standard (UHF EPC Gen 2, Class 1 compliant)

## 110XI4 600 DPI

### Printing Specifications

- 600 dpi resolution (23.62 dots / mm)
- Dot size (W × L): 0.0016" × 0.0016" (0.042 mm × 0.042 mm)
- First dot location measured from inside media edge: 0.08" ±0.05" (2.1 mm ±1.25 mm)
- Maximum print width: 2496 dots 4.16" (105.6 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 50" (1270 mm)
- Media registration tolerance\*:
  - Vertical:
    - ±0.030" (±0.75 mm) at print speeds at or below 4 ips on non-continuous media
    - ±0.060" (±1.5 mm) at print speeds higher than 4 ips
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 1.5, 2, 3, 4, 5, 6
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 1.6 mil to 16 mil
  - Ladder (rotated) orientation: 1.6 mil to 16 mil

### Media and Ribbon Specifications

- Media width (label and liner): 0.79" (20 mm) to 4.5" (114 mm)
- Minimum label length: See media specifications on page 2
- Maximum full-width media thickness for cutter: 0.009" (0.23 mm)
- Ribbon width: 0.79" (20 mm) to 4.33" (110 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 121 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 10.31" (261.9 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 50 lbs. (22.7 kg)
- RFID ready is standard (UHF EPC Gen 2, Class 1 compliant)

\*Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.

## 140XI4™ 203 DPI

### Printing Specifications

- 203 dpi resolution (8 dots / mm)
- Dot size (W × L): 0.0049" × 0.0049" (0.125 mm × 0.125 mm)
- First dot location measured from inside media edge: 0.10" ±0.035" (2.5 mm ±0.9 mm)
- Maximum print width: 1024 dots 5.04" (128 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 150" (3810 mm)
- Media registration tolerance\*:
  - Vertical:
    - ±0.030" (±0.75 mm) at print speeds at or below 4 ips on non-continuous media
    - ±0.060" (±1.5 mm) at print speeds higher than 4 ips
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 2.4, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 4.9 mil to 49 mil
  - Ladder (rotated) orientation: 4.9 mil to 49 mil

### Media and Ribbon Specifications

- Media width (label and liner): 1.57" (40 mm) to 5.51" (140 mm)
- Minimum label length: See media specifications on page 2
- Maximum full-width media thickness for cutter: 0.009" (0.23 mm)
- Ribbon width: 1.57" (40 mm) to 5.1" (130 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 180 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 11.31" (287.3 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 55 lbs. (25.0 kg)

## FONT MATRICES: 300 DPI (12 DOTS / MM) PRINTHEADS

Font	Matrix (in dots) (H × W)	Type†	Minimum Character Size (H × W) in inches (mm)	Max CPI
<b>A</b>	9 × 5	U-L-D	0.030 × 0.020 (0.76 × 0.51)	50.0
<b>B</b>	11 × 7	U	0.037 × 0.030 (0.94 × 0.76)	33.3
<b>C, D</b>	18 × 10	U-L-D	0.060 × 0.040 (1.5 × 1.0)	25.0
<b>E</b>	41 × 20	OCR-B	0.137 × 0.087 (3.5 × 2.2)	11.5
<b>F</b>	26 × 13	U-L-D	0.087 × 0.053 (2.2 × 1.3)	18.8
<b>G</b>	60 × 40	U-L-D	0.200 × 0.160 (5.1 × 4.1)	6.3
<b>H</b>	30 × 19	OCR-A	0.100 × 0.093 (2.5 × 2.37)	10.7
<b>GS</b>	24 × 24	SYMBOL	0.080 × 0.080 (2.03 × 2.03)	12.5
<b>P</b>	20 × 18	U-L-D	0.067 × 0.060 (1.69 × 1.52)	N / A
<b>Q</b>	28 × 24	U-L-D	0.093 × 0.080 (2.37 × 2.03)	N / A
<b>R</b>	35 × 31	U-L-D	0.117 × 0.103 (2.96 × 2.62)	N / A
<b>S</b>	40 × 35	U-L-D	0.133 × 0.117 (3.39 × 2.96)	N / A
<b>T</b>	48 × 42	U-L-D	0.160 × 0.140 (4.06 × 3.56)	N / A
<b>U</b>	59 × 53	U-L-D	0.197 × 0.177 (5.00 × 4.49)	N / A
<b>V</b>	80 × 71	U-L-D	0.267 × 0.237 (6.77 × 6.01)	N / A
<b>Ø</b>	variable	U-L-D	variable	N / A

† U = Uppercase L = Lowercase D = Descenders

\*Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.

## 170XI4™ 203 DPI

### Printing Specifications

- 203 dpi resolution (8 dots / mm)
- Dot size (W × L): 0.0049" × 0.0049" (0.125 mm × 0.125 mm)
- First dot location measured from inside media edge: 0.10" ±0.035" (2.5 mm ±0.9 mm)
- Maximum print width: 1344 dots 6.6" (168 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 150" (3810 mm)
- Media registration tolerance\*:
  - Vertical: ±0.060" (±1.5 mm) on non-continuous media
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 2.4, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 3.3 mil to 49 mil
  - Ladder (rotated) orientation: 3.9 mil to 39 mil

### Media and Ribbon Specifications

- Media width (label and liner): 2.0" (51 mm) to 7.1" (180 mm)
- Minimum label length: See media specifications on page 2
- Maximum full-width media thickness for cutter: 0.007" (0.18 mm)
- Ribbon width: 2.0" (51 mm) to 6.7" (170 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 220 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 13.31" (338.1 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 67 lbs. (30.5 kg)

## 170XI4 300 DPI

### Printing Specifications

- 300 dpi resolution (11.8 dots / mm)
- Dot size (W × L): 0.0033" × 0.0033" (0.084 mm × 0.084 mm)
- First dot location measured from inside media edge: 0.10" ±0.035" (2.5 mm ±0.9 mm)
- Maximum print width: 1984 dots 6.6" (168 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 100" (2540 mm)
- Media registration tolerance\*:
  - Vertical: ±0.060" (±1.5 mm) on non-continuous media
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 2.4, 3, 4, 5, 6, 7, 8
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 3.3 mil to 49 mil
  - Ladder (rotated) orientation: 3.9 mil to 39 mil

### Media and Ribbon Specifications

- Media width (label and liner): 2.0" (51 mm) to 7.1" (180 mm)
- Minimum label length: See media specifications on page 2
- Maximum full-width media thickness for cutter: 0.007" (0.18 mm)
- Ribbon width: 2.0" (51 mm) to 6.7" (170 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 220 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 13.31" (338.1 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 67 lbs. (30.5 kg)

\*Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.



## 220XI4™ 203 DPI

### Printing Specifications

- 203 dpi resolution (8 dots / mm)
- Dot size (W × L): 0.0049" × 0.0049" (0.125 mm × 0.125 mm)
- First dot location measured from inside media edge: 0.10" ±0.035" (2.5 mm ±0.9 mm)
- Maximum print width: 1728 dots 8.5" (216 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 150" (3810 mm)
- Media registration tolerance\*:
  - Vertical: ±0.060" (±1.5 mm) on non-continuous media
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 203 dpi: 2.4, 3, 4, 5, 6, 7, 8, 9, 10
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 4.9 mil to 49 mil
  - Ladder (rotated) orientation: 4.9 mil to 49 mil

### Media and Ribbon Specifications

- Media width (label and liner): 4.25" (108 mm) to 8.8" (224 mm)
- Minimum label length: See media specifications on page 2
- Maximum full-width media thickness for cutter: 0.005" (0.14 mm)
- Ribbon width: 4.25" (108 mm) to 8.6" (220 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 269 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 15.81" (393.7 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 72 lbs. (32.7 kg)

## 220XI4 300 DPI

### Printing Specifications

- 300 dpi resolution (11.8 dots / mm)
- Dot size (W × L): 0.0033" × 0.0033" (0.084 mm × 0.084 mm)
- First dot location measured from inside media edge: 0.10" ±0.035" (2.5 mm ±0.9 mm)
- Maximum print width: 2560 dots 8.5" (216 mm)
- Maximum non-continuous media print length (with 16 MB memory): 39" (991 mm)
- Maximum continuous media print length (with 16 MB memory): 100" (2540 mm)
- Media registration tolerance\*:
  - Vertical: ±0.060" (±1.5 mm) on non-continuous media
  - Horizontal: ±0.060" (±1.5 mm)
- Programmable print speeds (inches per second): 300 dpi: 2.4, 3, 4, 5, 6
- Barcode modulus "X" dimension:
  - Picket fence (non-rotated) orientation: 4.9 mil to 49 mil
  - Ladder (rotated) orientation: 4.9 mil to 49 mil

### Media and Ribbon Specifications

- Media width (label and liner): 4.25" (108 mm) to 8.8" (224 mm)
- Minimum label length: See media specifications on page 2
- Maximum full-width media thickness for cutter: 0.005" (0.14 mm)
- Ribbon width: 4.25" (108 mm) to 8.6" (220 mm)

### General Specifications

- Power consumption:
  - Idle = 20 W
  - Printing = 269 W (printing pause tests label at lowest speed)
  - Standby = 25 W
- Height: 15.5" (393.7 mm)
- Width: 15.81" (401.6 mm)
- Depth: 20.38" (517.5 mm)
- Weight: 72 lbs. (32.7 kg)

\*Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.



**ENVIRONMENTAL SPECIFICATIONS**

- Operating environment:
  - Thermal transfer = 40°F to 105°F (5° to 40°C)
  - Direct thermal = 32°F to 105°F (0° to 40°C)
  - 20% to 85% non-condensing relative humidity
- Storage / Transportation environment:
  - 40°F to 140°F (5° to 60°C)
  - 5% to 85% non-condensing relative humidity

**ELECTRICAL SPECIFICATIONS**

- Universal power supply with power-factor correction 90–264 VAC, 48–62 Hz
- Agency approvals: IEC 60950-1, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3
- Product Markings: cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark(Arg), CCC, GOST-R, BSMI, KCC, STB, and UkrSEPRO

**FONT MATRICES: 600 DPI (24 DOTS / MM) PRINTHEADS**

Font	Matrix (in dots) (H × W)	Type†	Minimum Character Size (H × W) in inches (mm)	Max CPI
<b>A</b>	9 × 5	U-L-D	0.015 × 0.010 (0.38 × 0.25)	100.0
<b>B</b>	11 × 7	U	0.018 × 0.015 (0.45 × 0.38)	66.7
<b>C, D</b>	18 × 10	U-L-D	0.030 × 0.020 (0.77 × 0.51)	50.0
<b>E</b>	82 × 40	OCR-B	0.137 × 0.087 (3.4 × 2.2)	11.54
<b>F</b>	26 × 13	U-L-D	0.043 × 0.027 (1.1 × 0.69)	37.5
<b>G</b>	60 × 40	U-L-D	0.100 × 0.080 (2.5 × 2.0)	12.5
<b>H</b>	60 × 38	OCR-A	0.100 × 0.093 (2.5 × 2.4)	10.71
<b>GS</b>	24 × 24	SYMBOL	0.040 × 0.040 (1.0 × 1.0)	25.0
<b>P</b>	20 × 18	U-L-D	0.033 × 0.030 (0.85 × 0.77)	N / A
<b>Q</b>	28 × 24	U-L-D	0.047 × 0.040 (1.19 × 1.02)	N / A
<b>R</b>	35 × 31	U-L-D	0.059 × 0.052 (1.49 × 1.32)	N / A
<b>S</b>	40 × 35	U-L-D	0.067 × 0.059 (1.70 × 1.49)	N / A
<b>T</b>	48 × 42	U-L-D	0.080 × 0.070 (2.04 × 1.79)	N / A
<b>U</b>	59 × 53	U-L-D	0.099 × 0.089 (2.51 × 2.25)	N / A
<b>V</b>	80 × 71	U-L-D	0.134 × 0.199 (3.40 × 5.06)	N / A
<b>Ø</b>	variable	U-L-D	variable	N / A

† U = Uppercase L = Lowercase D = Descenders

For more information, visit [www.zebra.com/xi4](http://www.zebra.com/xi4)



**NA and Corporate Headquarters**  
+1 800 423 0442  
inquiry4@zebra.com

**Asia-Pacific Headquarters**  
+65 6858 0722  
contact.apac@zebra.com

**EMEA Headquarters**  
zebra.com/locations  
mseurope@zebra.com

**Latin America Headquarters**  
+1 847 955 2283  
la.contactme@zebra.com