

ZEBRA® PRODUCT COMPARISON

4-INCH-WIDE INDUSTRIAL PRINTERS



SEE MORE. DO MORE.



ZT220™



ZT230™



ZT410™



105SLPlus™



110Xi4™

MODEL		ZT220™	ZT230™	ZT410™	105SLPlus™	110Xi4™
QUICK FACTS	MAX. PRINT WIDTH	4.09"/ 104mm	4.09"/ 104mm	4.09"/ 104mm	4.09"/ 104mm	4.09"/ 104mm
	PRINTHEAD RESOLUTION	203, 300 dpi	203, 300 dpi	203, 300, 600 dpi	203, 300 dpi	203, 300, 600 dpi
	MAX. PRINT SPEED	6"/ 152mm per second	6"/ 152mm per second	14"/ 356mm per second	12"/ 305mm per second	14"/ 356mm per second
	PRINTER LANGUAGES	ZPL®, XML	ZPL, XML	ZPL, EPL™, XML	ZPL, XML	ZPL, XML
	STANDARD CONNECTIVITY	Serial, USB 2.0	Serial, USB 2.0	Serial, USB 2.0, 10/100 Ethernet, Bluetooth® 2.1, USB Host	Serial, Parallel, USB 2.0, 10/100 Ethernet	Serial, Parallel, USB 2.0, 10/100 Ethernet
	OPTIONAL CONNECTIVITY	Parallel, Ethernet, wireless	Parallel, Ethernet, wireless	Parallel, wireless	Wireless	Wireless, twinax, coax
PRINTER FEATURES	LCD DISPLAY		✓	✓	✓	✓
	PRINTER CONSTRUCTION MATERIAL	Plastic/ Metal	Metal	Metal	Metal	Metal
	STANDARD FLASH (TOTAL)	128MB	128MB	256MB	8MB	8MB
	STANDARD RAM (TOTAL)	128MB	128MB	512MB	16MB	16MB
	RFID-READY			✓		✓
PHYSICAL FEATURES	FOOTPRINT (D x W x H)	17" x 9.4" x 11"/ 432mm x 239mm x 280mm	17" x 9.5" x 10.9"/ 432mm x 242mm x 277mm	19.5" x 10.6" x 12.75"/ 495mm x 269mm x 324mm	20.38" x 10.31" x 15.5"/ 517.5mm x 261.9mm x 393.7mm	20.38" x 10.31" x 15.5"/ 517.5mm x 261.9mm x 393.7mm
	WEIGHT	17 lbs/ 7.8kg	20 lbs/ 9.1kg	36 lbs/ 16.33kg	50 lbs/ 22.7kg	50 lbs/ 22.7kg
MEDIA	MIN. MEDIA WIDTH	0.75"/ 19.4mm	0.75"/ 19.4mm	1"/ 25.4mm	0.79"/ 20mm	0.79"/ 20mm
	MEDIA HANDLING OPTIONS	Peel, cutter	Peel, cutter, liner rewind	Peel, full rewind, cutter	Peel, full rewind, cutter	Peel, full rewind, cutter
	MAX. RIBBON LENGTH	300m	450m	450m	450m	450m

GAIN MORE REVENUE FROM GENUINE ZEBRA™ SUPPLIES

Offering the largest selection of pre-tested, high-quality labels, tags, receipt paper, wristbands, cards and ribbons, Zebra can provide a solution for virtually any application.

- Supplies are extensively tested to ensure print quality, chemical resistance and adhesive strength.

- We use consistent manufacturing and quality processes to ensure customer satisfaction.

- We never substitute materials ensuring crisp, readable and scannable output without needing to adjust printer settings.

- We have the ability to create custom supplies in any size with pre-printed text, graphics and logos.

Product Name		Thermal Transfer/ Direct Thermal	Description and Key Features	Government	Logistics	Healthcare	Manufacturing	Retail	Suggested Ribbon (standard)	Suggested Ribbon (high durability)
Labels	Z-Perform™ 1000D	DT	Uncoated bright-white paper label with a permanent acrylic adhesive; limited resistance to moisture or abrasion; not recommended for high-print-speed applications		✓					
	Z-Perform 2000D	DT	Bright-white, smooth paper label with a permanent acrylic adhesive; meets FDA 175.105 indirect food contact requirements		✓		✓	✓		
	Z-Perform 2000T	TT	Bright-white, smooth paper label with an all-temp acrylic adhesive		✓				2000, 5319	5555, 3200
	Z-Select™ 4000D	DT	Premium, bright-white, ultra-smooth paper label with permanent acrylic adhesive; meets FDA 175.105 indirect food contact requirements; ideal for high-speed printing applications		✓	✓	✓	✓		
	Z-Select 4000T	TT	Premium, bright-white, ultra-smooth paper label with all-temp acrylic adhesive; meets FDA 175.105 indirect food contact requirements; ideal for high-speed printing applications		✓		✓		2000, 2100, 5319	5555, 3200
	Z-Select 4000T Removable	TT	Premium, bright-white, ultra-smooth paper label with a removable acrylic adhesive for applications requiring clean removability without damaging the label or the surface; meets FDA 175.105 indirect food contact requirements		✓		✓	✓	2000, 2100, 5319	5555, 3200
	PolyPro 3000T	TT	White, matte polypropylene with a permanent acrylic adhesive; meets FDA 175.105 indirect food contact requirements		✓	✓	✓		5555, 3200	5095
	PolyPro 4000T	TT	White, matte Kimdura® polypropylene label with a permanent acrylic adhesive; CSA acceptances; meets FDA 175.105 indirect food contact requirements	✓	✓		✓		5555, 3200	5586
	Z-Ultimate® 2000T White	TT	White, gloss polyester label with a permanent acrylic adhesive; UL/cUL acceptances				✓		5095	5100
	Z-Ultimate 4000T White	TT	White, gloss polyester label with a high-performance permanent acrylic adhesive; UL/cUL and CSA acceptances	✓			✓		5095	5100
	Z-Supreme™ 2000T White	TT	White, gloss polyimide label with a high-temp permanent acrylic adhesive that provides resistance to harsh environments				✓			5100
Z-Slip™	DT	Direct thermal paper tag combined with a clear polypropylene label featuring a permanent acrylic adhesive; replaces standard packing list and packing list envelope		✓						
Tags	Z-Select 4000T 7.0 mil Tag	TT	Premium, bright-white, ultra-smooth paper tag					✓	2000, 2100, 5049, 5319	



ASIA-PACIFIC HEADQUARTERS
Zebra Technologies Asia Pacific Pte Ltd

71 Robinson Road, #05-02/03, Singapore 068895 T: 65 6858 0722 F: 65 6885 0838

Asia-Pacific Sales Representations: Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, New Zealand, Philippines, South Korea, Singapore, Thailand, Taiwan, Vietnam

Other Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom

Latin America: Brazil, Florida (LA Headquarters in USA), Mexico **Middle East & Africa:** Dubai, South Africa

SEE MORE.
DO MORE.

www.zebra.com

(4/14)ROA