

## PolyPro 3000T Matte High Tack

<b>Media Type</b>	Label	✓	<b>Film Type</b>	Polyethylene	
	Receipt			Polyolefin	
	Tag			Polypropylene	✓
	Wristband			Polyester	
<b>Material Type</b>	Paper		Polyimide		
	Synthetic	✓	<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			Deep Freeze	
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
<b>Adhesive Type</b>	Permanent	✓		Ultra High Temperature	
	Removable			High Tack	✓
	No Adhesive			Chemical Resistance	-
<b>Finish</b>	Matte	✓	<b>Environment</b>	Indoor	✓
	Gloss			Outdoor	

### Additional Features

- Bi-axially orientated polypropylene film
- Strong rubber-based adhesive for excellent adhesion to a wide variety of surfaces
- Tear and water resistant
- Good low temperature performance when applying to cold and damp surfaces
- Offers good adhesion to a wide variety of surfaces
- Adhesive complies with Isega for direct contact with dry and non-fatty foods

### Suggested Applications

- Industrial product labelling
- Pallet wrap labels
- Labels which can be recycled with other polypropylene substrates
- Labelling of most packaging materials and plastic substrates
- Shelf edge labels
- Medium-life product and box labelling

## Technical Specifications

	Description	Caliper
<b>Facestock</b>	Matte white topcoated polypropylene film	66 microns
<b>Adhesive</b>	Permanent rubber adhesive	10 microns
<b>Liner</b>	60gsm glassine liner	54 microns
	<b>Total</b>	<b>130 microns ±10%</b>

**Recommended Zebra Printers:** Desktop, mid-range and high-performance thermal printers

**Recommended Zebra Ribbons:** 3200, 4800, 5095

**Minimum Application Temperature:** 0°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -20°C to 50°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 20°C at 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, up to 1 year  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE17719.

Supplies are warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For the complete warranty statement, please visit: [www.zebra.com/warranty](http://www.zebra.com/warranty)